

Dy-Mark PROTECH® Dry Graphite Lubricant



Dy-Mark PROTECH® Dry Graphite Lubricant is a multi-purpose dry powder lubricant that provides lubrication to surfaces which require unhindered sliding capability. Use on metal, wood or plastic.

DIRECTIONS FOR USE

Recommended Uses:

Door locks, hinges, zippers, latches and other uses.

Application:

Shake can for at least 45 seconds AFTER the mixing ball begins to rattle. Shake can occasionally during use. Clean and dry surface area thoroughly. Spray can in UPRIGHT position only. Spray light even coat directly onto surfaces. Repeat application if necessary. Use extension tube for hard to reach areas.

TECHNICAL DATA

Size:	150g Aerosol
Colour:	Black
Consistency:	Powder
Propellant:	DME

STORAGE

Store below 50C. Do not store in direct sunlight or in vehicles under hot conditions.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents under pressure. Do not puncture or incinerate, even when empty.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye Contact: Rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (Australia: 13 11 26; New Zealand: 0800 764 766).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.