TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd PO Box 1556 • Toowong 4066 • Phone: 1300 396 275 • Fax: 1300 360 440 www.dvmark.com.au



Dy-Mark PROTECH® Silicone Lubricant



Dy-Mark PROTECH® Silicone Lubricant is a high performance multi-purpose silicone spray that protects, waterproofs and lubricates. It provides a thin, clear protective film which is non staining and non-corrosive. For use on metal, plastic, rubber and wood. Can work in extreme temperatures of -40degC to +260degC.

Incorporates patented 2-way actuator with locking tab.

DIRECTIONS FOR USE

Recommended Uses:

Pulleys, pipes, hinges, conveyers, belts, tracks, bearings, doors, hoists and other uses.

Application:

Shake can well. Shake can occasionally during use. Spray can in UPRIGHT position only. Spray light even film. Use extension tube for hard to reach areas. Repeat application if necessary. When finished spraying, actuator can be set in lock position to prevent accidental actuation.

Prolonged exposure to vinyl & rubber not recommended.

TECHNICAL DATA	
Size: Colour:	350g Aerosol Clear
Consistency:	Liquid
Propellant:	Hydrocarbon

STORAGE

Store below 50C. Do not store in direct sunlight or in vehicles under hot conditions.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents under pressure. Do not puncture or incinerate, even when empty.

SAFETY INFORMATION HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye Contact: Rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (Australia: 13 11 26; New Zealand: 0800 764 766).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.