

Dy-Mark PROTECH® Penetrating Oil



Dy-Mark PROTECH® Penetrating Oil is a high speed penetrant and lubricant that quickly penetrates rusted and seized metal parts. It has a low viscosity that creeps into cracks, seams, threads and joints, loosening and freeing them instantly.

Incorporates patented 2-way actuator with locking tab. Uses a 360° valve for upright inverted applications.

DIRECTIONS FOR USE

Recommended Uses:

Taps, nuts & bolts, rusted bolts, padlocks, pins, screws, bushings, clips, hinges, locks, washers and other rusted surfaces.

Application:

De-activate and isolate equipment before use. Shake can well. Shake can occasionally during use. 360 degree valve enables spraying in upright and inverted positions. Do not spray at 45 degree angle. Spray liberal coating directly on to corroded surfaces, saturating the problem area. Use extension tube for hard to reach areas. Repeat application if necessary.

When finished spraying, actuator can be set in lock position to prevent accidental actuation.

TECHNICAL DATA

Size:	400g Aerosol
Colour:	Light Golden yellow
Consistency:	Liquid
Propellant:	Carbon Dioxide

STORAGE

Store below 50C. Do not store in direct sunlight or in vehicles under hot conditions.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents under pressure. Do not puncture or incinerate, even when empty.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye Contact: Rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (Australia: 13 11 26; New Zealand: 0800 764 766).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.