



Dy-Mark PROTECH® Heavy Duty Degreaser



Dy-Mark PROTECH® Heavy Duty Degreaser has been specially formulated to provide effective and fast removal of tough grease, oil, dirt and grime. It delivers a concentrated jet which works immediately on contact and is easy to rinse off with water. For use on tools, machinery and equipment.

Uses a 360° valve for upright inverted applications.

DIRECTIONS FOR USE

Recommended Uses:

Engines, Machinery, Lifts and Hoists, tools, industrial equipment, farm equipment, Lawn mowers, garage floors and other uses.

Application:

Shake can well. Shake can occasionally during use. 360 degree valve enables spraying in upright and inverted positions. Do not spray at 45 degree angle. Hold can 20 - 25cms from surface. Spray liberal coating directly on to surface, saturating the problem area. Allow to penetrate for 5 - 10 minutes.

Hose off with pressure. Heavy or thick deposits may have to be loosened with a scraper or brush. Repeat application if necessary.

Prolonged exposure to painted metal surfaces not recommended.

TECHNICAL DATA

Size:	400g Aerosol
Colour:	Light yellow
Consistency:	Liquid
Propellant:	Carbon Dioxide

STORAGE

Store below 50C. Do not store in direct sunlight or in vehicles under hot conditions.

DISPOSAL

Aerosol should be completely emptied prior to disposal. Contents under pressure. Do not puncture or incinerate, even when empty.

SAFETY INFORMATION

HIGHLY FLAMMABLE

Keep away from flame, heat and sources of ignition. Do not smoke and ensure adequate ventilation during use. Harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

FIRST AID

KEEP OUT OF REACH OF CHILDREN

If swallowed: Do not induce vomiting.

Eye Contact: Rinse immediately with plenty of water. Seek medical advice from your doctor or Poisons Information Centre (**Australia:** 13 11 26; **New Zealand:** 0800 764 766).

Note: the information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface type and environmental conditions. Refer to Material Safety Data Sheet for more information.