

# OVERRIDE



1650515 • Clear wrap around frame



1650516 • Smoke wrap around frame



45 g

**+ CLOSE FITTING HIGH CONTOUR DESIGN  
FOR IMPROVED EYE PROTECTION**



**+ FITS OVER PRESCRIPTION SPECTACLES TO  
PROVIDE MEDIUM IMPACT PROTECTION**

**+ SINGLE PIECE POLYCARBONATE DISTORTION FREE LENS**

**+ ADJUSTABLE TEMPLE ARMS FOR  
A SECURE, COMFORTABLE FIT**

**bolle**  
SAFETY

# OVERRIDE

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
<b>OVERRIDE</b>	 Clear	1650515	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1650516	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

## LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

## OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 3. Range of luminous transmittance 8-18% (smoke & polarised).

## APPLICATIONS

- Assembly/production work
- Light engineering
- Laboratory work

## MAIN MARKETS

- Manufacturing
- Government
- Schools and Universities
- Medical and dental

## LENSES

- 2 mm polycarbonate
- 'ALS' anti-fog/anti-scratch coating on both sides of the lens
- 100% UV385: Clear

## CLEANING AND STORAGE

**CLEANING :** Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** Store between 5 and 40 °, humidity <90%.

## CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	Hydrated Nylon frame front
TEMPLES	PC temple arms + EVA temple
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

## FRAME MARKING

**AS/NZS 1337.1.2010 :** Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

## ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: safety@bolle.com.au

## NEW ZEALAND:

Bollé New Zealand Limited  
Unit 5, 114 Sawyers Arms Road  
Papanui, Christchurch 8052  
T: 03 3751400  
E: bolle@bolle.co.nz