

ELITE DOUBLE LEG ADJUSTABLE LANYARD

PART CODE: **WLA2**



**HEIGHT
SAFETY**

PRODUCT INFORMATION >

Double Leg Adjustable Lanyard + hardware (Refer to double leg lanyard hardware page)

PRODUCT FEATURES >

- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 160kg including tools and equipment.
- Drop forged lanyard hardware.
- Stitching patterns are sewn by computer controlled bar tacking machinery for precision using UV resistant high tenacity polyester yarn with 100 newton (10kg) breaking strength.
- Unique THETA stitch pattern has 423 stitches resulting in a strength that matches the lanyard's webbing strength.
- Adjusts - 0.9m to 2m.
- Ideal for situations that require length adjustment.

PRODUCT DETAILS >

- AUS/NZ designed engineered and MADE.
- Webbing Tenacity= 33kN.
- Webbing is UV rated to meet AS/NZS 1891.1 standard.
- 'THETA' stitch pattern (equals 3300kg strength). Engineered to match webbing strength to ensure no weak point in the harness assembly.
- Contrast stitch thread colour for easy inspection.
- Standard LINQ shock absorber is rated for wearer of up to 160kg. Including tooling and equipment.
- Drop forged D Transition point doubles as a spare leg stowage point.
- Adjusts - 0.9m to 2m.
- **Webbing Material: Polyester**; 45mm; UV Resilient; Solvent Resistant
- **Fall Arrest Hardware:** Drop Forged corrosion resistant electrophoresis high strength alloy steel
- **Stitch Pattern:** THETA Pattern combines 423 stitches to exceed 33kN of strength; AS/NZ compliant colour contrast.
- **Web Tenacity:** Min 30kN Max 33kN.

STANDARDS >



AS/NZS 1891.1:2007
BMP 713822
BMP 713823
Australian Standard



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM



DOUBLE LEG LANYARD HARDWARE



FOR COMPLETE CODE ADD LANYARD & HARDWARE CODE TOGETHER

EG. DOUBLE LEG ADJUSTABLE LANYARD WITH 3 X TRIPLE ACTION KARABINERS = WLA2 + KTKT

KDKD >



3 x Double Action Karabiners

KDSD >



1 x Double Action Karabiner
2 x Double Action Scaff Hooks

KDSN >



1 x Double Action Karabiner
2 x Snap Hooks

KDST >



1 x Double Action Karabiner
2 x Triple Action Scaff Hooks

KTKT >



3 x Triple Action Karabiners

KTSD >



1 x Triple Action Karabiner
2 x Double Action Scaff Hooks

KTSN >



1 x Triple Action Karabiner
2 x Snap Hooks

KTST >



1 x Triple Action Karabiner
2 x Triple Action Scaff Hooks

SNKT >



1 x Snap Hook
2 x Triple Action Karabiners

SNSD >



1 x Snap Hook
2 x Double Action Scaff Hooks

SNSN >



3 x Snap Hooks

SNST >



1 x Snap Hook
2 x Triple Action Scaff Hooks

KSKD >



1 x Screw Gate Karabiner
2 x Double Action Karabiners

KSSN >



1 x Screw Gate Karabiner
2 x Snap Hooks

KSSD >



1 x Screw Gate Karabiner
2 x Double Action Scaff Hooks

KSST >



1 x Screw Gate Karabiner
2 x Triple Action Scaff Hooks

KSKS >



3 x Screw Gate Karabiners

SNTSNT >



3 x Triple Action Snap Hooks

SNTST >



1 x Triple Action Snap Hook
2 x Double Action Scaff Hooks

SNGS >



1 x Triple Action Snap Hook
2 x Triple Action Scaff Hooks

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM