



UN 1170 ETHYL ALCOHOL

SAFETY DATA SHEET

HAZARDOUS SUBSTANCE, DANGEROUS GOODS

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

<https://www.legislation.gov.au/Details/F2019C00625/Html/Text>

section 1 applicable product

TGA exempt

WHO https://www.who.int/gpsc/5may/Guide_to_Local_Production.pdf

LIQUID CARE Instant hand Sanitiser kills 99.9% of germs without the need for water. It is non-sticky formula leaves you feeling cleansed and refreshed, with the added moisturising ingredients for your smoother skin. Use anywhere for instant action.

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word

Danger

Hazard Classifications

Flammable Liquids - Category 2

Serious Eye Damage/irritation - Category 2A



Hazard Statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Prevention Precautionary Statements

PI 02 Keep out of reach of children.

PI 03 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P243 Take precautionary measures against static discharge.

Response Precautionary Statements p 101

If medical advice is needed, have product container or label at hand.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Storage Precautionary Statement

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule: S5. Caution

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

Classified as a Cl (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

DIRECTION FOR USE: Apply a small amount to hands and rub hands together thoroughly until dry.

WARNING; FLAMMABLE LIQUID, KEEP AWAY FROM HEAT AND FLAME. FOR EXTERNAL USE ON HANDS ONLY. KEEP OUT OF REACH OF CHILDREN. KEEP OUT OF EYES. IF PRODUCT GETS INTO EYES RINSE WELL WITH WARM WATER. DISCONTINUE USE IF SKIN IRRITATION OCCURS. IF SWALLOWED SEEK MEDICAL ADVICE.



UN 1170 ETHYL ALCOHOL

SAFETY DATA SHEET

HAZARDOUS SUBSTANCE, DANGEROUS GOODS

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Ethanol	64-17-5	> 72 % (w/v) 0
Ingredients determined to be non-hazardous	-	Balance

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazchem Code: +2YE

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Highly flammable liquid and vapour. Combustible liquid. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. DO NOT SMOKE

Firefighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up but avoid generating dust. Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: 14



UN 1170 ETHYL ALCOHOL

SAFETY DATA SHEET

HAZARDOUS SUBSTANCE, DANGEROUS GOODS

7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

Classified as a Cl (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations. This material is a Scheduled Poison Schedule 5 (Caution) and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS 1 PERSONAL PROTECTION

National occupational exposure limits:

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 Minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sen' Notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Avoid generating and inhaling dusts. Use with local exhaust ventilation or while wearing dust mask. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

Personal Protection Equipment: SAFETY SHOES, SAFETY GLASSES.

Wear safety shoes, safety glasses.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Material Family:	Organic Material
Base Units:	Litres
Form:	Liquid
Colour:	Colourless
Odour:	Alcohol
Solubility:	Miscible in water
Specific Gravity (20 o c):	0.95
Relative Vapour Density (air=1):	1.59 @150 C
Vapour Pressure (20 Q C):	5.9 kPa
Flash Point CC):	25
Flammability Limits (%):	4 - 20
Autoignition Temperature CC): Melting Point/Range CC):	392
Boiling Point/Range CC):	80
pH:	7 - 8
Viscosity:	Approx. 6000 cSt
Total VOC (g/Litre):	98 %

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable



UN 1170 ETHYL ALCOHOL

SAFETY DATA SHEET

HAZARDOUS SUBSTANCE, DANGEROUS GOODS

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Avoid exposure to heat, sources of ignition, and open flame

Incompatible materials: Incompatible with oxidising agents, acids, acid chlorides, alkali metals, ammonia, potassium tert-butoxide.

Hazardous decomposition products: Hazardous polymerisation will not occur.

Hazardous reactions: Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label.

Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation:	Material may be an irritant to mucous membranes and respiratory tract.
Skin contact:	Contact with skin may result in irritation.
Ingestion:	Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.
Eye contact:	An eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Acute toxicity

Inhalation:	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >5 mg/L
LC50 (Rat):	5,900 mg/m ³ /6hr (Ethanol)
Skin contact:	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): mg/Kg
Ingestion:	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): mg/Kg
LD50 (Rat):	7060 mg/kg (Ethanol)
Corrosion/Irritancy:	Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as not corrosive or irritating to skin.
Sensitisation:	Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.
Aspiration hazard:	This material has been classified as non-hazardous.
Specific target organ toxicity (single exposure):	This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity:	This material has been classified as non-hazardous.
Carcinogenicity:	This material has been classified as non-hazardous.
Reproductive toxicity (including via lactation):	This material has been classified as non-hazardous.
Specific target organ toxicity (repeat exposure):	This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard:	This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): > 100 mg/L
Long-term aquatic hazard:	This material has been classified as non-hazardous, Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): > 100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log Kow < 4.
Ecotoxicity:	No information available.
Persistence and degradability:	The product is readily biodegradable.
Bio-accumulative potential:	Risk of bioaccumulation in an aquatic species is low.
Mobility:	No information available.



UN 1170 ETHYL ALCOHOL

SAFETY DATA SHEET

HAZARDOUS SUBSTANCE, DANGEROUS GOODS

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible, material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION



ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN No: 1170

Dangerous Goods Class: Packing Group: 3

Hazchem Code: •2YE

Emergency Response Guide No: 14

Proper Shipping Name: ETHANOL SOLUTION

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.



MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea,

UN No: 1170

Dangerous Goods Class: Packing Group: 3

Proper Shipping Name: ETHANOL SOLUTION



AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1170

Dangerous Goods Class: Packing Group: 3

Proper Shipping Name: ETHANOL SOLUTION

15. REGULATORY INFORMATION

This material/constituent(s) is covered by the following requirements:

- The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth).
- All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (ACS).

16. OTHER INFORMATION

Reason for issue: Format change

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.