

SIDEWINDER



23 g



1615501 • Clear Lens



1615502 • Smoke Lens



1615503 • Amber Lens



1615504 • Dark ESP Lens



1615505 • Bronze Lens









1652107 • Grey Polarised Lens

- + HIGH GLOSS, DARK GUN METAL DUAL MATERIAL FRAME
- +  PLATINUM COATING ()
- + RUBBER NOSE PADS FOR SUPERIOR COMFORT AND NON-SLIP FIT
- + HALF FRAME DUAL LENS DESIGN

bollé
SAFETY

SIDEWINDER

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
SIDEWINDER	 Clear Lens	1615501	IO & b	AS/NZS 1337.1.2010	Platinum P
	 Smoke Lens	1615502	I3 & b	AS/NZS 1337.1.2010	Platinum P
	 Amber Lens	1615503	IO & b	AS/NZS 1337.1.2010	Platinum P
	 ESP Lens	1615504	I1 & b	AS/NZS 1337.1.2010	Hard coat
	 Bronze Lens	1615505	I3 & b	AS/NZS 1337.1.2010	Platinum P
	 Grey Polarised Lens	1652107	I2 & b	AS/NZS 1337.1.2010	Hard coat

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses
- b**. Manufacturer name

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 -88% (twilight).
- 2. Range of luminous transmittance 18-43% (flash).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Driving
- Solar UV exposure
- Emergency response
- Rigging
- Laboratory and dental work

MAIN MARKETS

- Manufacturing
- Local government and councils
- Utilities: power, gas, water and roads
- Medical and dental
- Transport
- Mining
- Construction
- Dental

LENSES

- New moulded lenses
- 2mm polycarbonate
- 8 base curve
- Platinum coating on both sides of Clear, Smoke, Amber and Bronze lenses
- Hard coating on the ESP lens
- 100% UV 385 – Clear
- 100% UV 400 – Smoke, Amber, ESP and Bronze lenses

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz

SIDEWINDER

 PLATINUM



1615501

RANGE

-  1615501 : Clear Lens
-  1615502 : Smoke Lens
-  1615503 : Amber Lens
-  1615504 : Dark ESP Lens
-  1615505 : Bronze Lens
-  1652107 : Grey Polarised Lens

APPLICATIONS:

- Assembly and production work
- Driving
- Solar UV exposure
- Emergency response
- Rigging
- Laboratory and dental work

TECHNICAL SPECIFICATIONS

FRAME :

Painted, high gloss, dual material frame. Polycarbonate frame front, with new flat pad temple tips.

WEIGHT:

23 Grams

LENSES

- New moulded lenses
- 2mm polycarbonate
- 8 base curve
- Platinum coating on both sides of Clear, Smoke, Amber and Bronze lenses
- Hard coating on the ESP lens
- 100% UV 385 – Clear
- 100% UV 400 – Smoke, Amber, ESP and Bronze lenses

MAIN MARKETS:

- Manufacturing
- Mining
- Construction
- Local government and councils
- Utilities: power, gas and water
- Transport
- Medical and dental

STANDARDS:

Approved to AS/NZS 1337.1.2010. for Medium Impact Protection.

CLEANING INSTRUCTIONS:

Bolle Safety recommends only using our **CLEAN** Lens cleaning system.

FEATURES & BENEFITS

- High gloss, dark gun metal dual material frame.
- Polycarbonate frame front and new flat pad temple tips for improved comfort and fit
- Rubber nose pads for superior comfort and non-slip fit
- Half frame dual lens design providing extensive eye coverage
- Exceptional visual clarity through an 8 base curve distortion free lens
- **Highlight Feature:** New Platinum coating - A high performance anti fog and anti scratch coating guaranteeing greater safety, reliability and comfort.