

TRACKER 2



1652001 • Clear Lens



1652002 • Smoke Lens



1652010 • Twilight Lens



1652007 • Polarised Lens



Accessories:
1652015 • Rx Adaptor

Tracker 2 Welding also available:
1652016 • Shade 3
1652017 • Shade 5











50 g

- + CAN BE FITTED WITH AN RX PRESCRIPTION LENS**
- + 8 BASE CURVE**
- + RUBBERISED EYE SEAL PROVIDES EXCEPTIONAL PROTECTION AGAINST DUST AND OTHER PARTICLES**
- + ADJUSTABLE HEAD STRAP**

bolle
SAFETY

TRACKER 2

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
TRACKER 2	 Clear	1652001	I0 & 	AS/NZS 1337.1.2010	AF / AS
	 Smoke	1652002	I3 & 	AS/NZS 1337.1.2010	AF / AS
	 Twilight	1652010	I1 & 	AS/NZS 1337.1.2010	AF / AS
	 Grey Polarised	1652007	I2 & 	AS/NZS 1337.1.2010	Hardcoat

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses
- . Manufacturer name

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 -88% (twilight).
- 2. Range of luminous transmittance 18-43% (flash & polarised).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Dust protection
- Engineering/process work
- Solar UV exposure
- Milling
- Rigging
- Laboratory work


MAIN MARKETS

- Mining
- Manufacturing
- Construction
- Local Government/Councils
- Utilities: power, gas and water boards
- Petro Chemical

LENSES

- 2mm polycarbonate
- 8 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lenses: Clear, Smoke and Twilight
- 100% UV 385 – Clear
- 100% UV 400 – Smoke, Twilight and Polarised

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our  Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s. Meets the requirements of splash approval when used with the supplied head strap correctly adjusted.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz

TRACKER 2



1652001



RANGE



1652001 • Clear Lens



1652002 • Smoke Lens



1652010 • Twilight Lens



1652007 • Polarised Lens

APPLICATIONS :

- Dust protection
- Engineering/process work
- Solar UV exposure
- Milling
- Rigging
- Laboratory work

TECHNICAL SPECIFICATIONS

FRAME :

Matt black polycarbonate frame with midgrey rubber temple tips and EVA foam eye cups. Fitted with a 19mm elastic head strap.

WEIGHT :

50 Grams

LENSES :

- 2mm polycarbonate
- 8 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lenses: Clear and Smoke, Twilight, Shade 3 and Shade 4
- 100% UV 385 – Clear
- 100% UV 400 – Smoke, Twilight and Polarised

MAIN MARKETS :

- Mining
- Manufacturing
- Construction
- Local Government/Councils
- Utilities: power, gas and water boards
- Petro Chemical

STANDARDS :

Approved to AS/NZS 1337.1.2010. for Medium Impact Protection. Meets the requirements of splash approval when used with the supplied head strap correctly adjusted.

CLEANING INSTRUCTIONS :

Bolle Safety recommends only using our **CLEAN** Lens cleaning system.

FEATURES & BENEFITS

- Polycarbonate frame ensures excellent durability to strength
- Rubber temple tips provide greater comfort and a secure fit
- An adjustable head strap improves fit and protection
- 'ALS' anti-fog/anti-scratch coating on both sides of Clear, Smoke, Twilight, Shade 3 and Shade 5
- Exceptional visual clarity through an 8 base curve, distortion free lens
- Rubberised eye seal provides exceptional protection against dust and other particles
- **Highlight Feature:** Can be fitted with an Rx prescription lens whilst maintaining medium impact protection approval.